

 Sughrue

SUGHRUE MION, PLLC

JC13 Rec'd PCT/PTO

November 30, 2001

BOX PCTCommissioner for Patents
Washington, D.C. 20231PCT/GB00/02028
-filed May 26, 2000

Re: Application of Andrew G. RICKMAN and Arnold P. R. HARPIN
WAVEGUIDE JUNCTION WITH SILICON NITRIDE
Assignee: **BOOKHAM TECHNOLOGY PLC**
Our Ref: Q67482

Dear Sir:

The following documents and fees are submitted herewith in connection with the above application for the purpose of entering the National stage under 35 U.S.C. § 371 and in accordance with Chapter I of the Patent Cooperation Treaty:

- ☒ Information Disclosure Statement and PTO form 1449.
- ☒ a Preliminary Amendment

The Declaration and Power of Attorney, Assignment, will be submitted at a later date.

It is assumed that copies of the International Application, the International Search Report, the International Preliminary Examination Report, and any Articles 19 and 34 amendments as required by § 371(c) will be supplied directly by the International Bureau, but if further copies are needed, the undersigned can easily provide them upon request.

The Government filing fee is calculated as follows:

Total claims	<u>30</u>	-	20	=	<u>10</u>	x	\$18.00	=	<u>\$180.00</u>
Independent claims	<u>3</u>	-	3	=	<u></u>	x	\$84.00	=	<u>\$0.00</u>
Base Fee									<u>\$890.00</u>

TOTAL FEE \$1070.00

A check for the statutory filing fee of \$1070.00 is attached. You are also directed and authorized to charge or credit any difference or overpayment to Deposit Account No. 19-4880. The Commissioner is hereby authorized to charge any fees under 37 C.F.R. §§ 1.16, 1.17 and 1.492 which may be required during the entire pendency of the application to Deposit Account No. 19-4880. A duplicate copy of this transmittal letter is attached.

Priority is claimed from:

Country

Great Britain


Application No

9912737.5

Filing Date

June 1, 1999

Respectfully submitted,

Robert J. Seas, Jr.
Registration No. 21,092

RJS/slb

20001130 14:00:00

PATENT APPLICATION

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application of

Andrew G. RICKMAN, et al.

Appln. No.: NOT YET ASSIGNED

Confirmation No.: NOT YET ASSIGNED

Group Art Unit: NOT YET ASSIGNED

Filed: November 30, 2001

Examiner: NOT YET ASSIGNED

For: WAVEGUIDE JUNCTION WITH SILICON NITRIDE

PRELIMINARY AMENDMENT

Commissioner for Patents
Washington, D.C. 20231

Sir:

Prior to examination, please amend the above-identified application as follows:

IN THE CLAIMS:

Please enter the following amended claims:

3. A junction structure according to claim 1, wherein the dielectric layer below the further waveguide region is silicon dioxide.
4. A junction structure according to claim 2, wherein the substrate comprises a layer of silicon dioxide and a layer of silicon.
5. A junction structure according to any of claim 2, wherein the dielectric layer also extends over the light transmitting semiconductor layer.
7. A junction structure according to any of claim 2, wherein there is provided an anti-reflective layer over said end face.

9. A junction structure according to claim 7, wherein the light transmitting semiconductor layer is directly covered by a layer of silicon dioxide on the side remote from the substrate.

10. A junction structure according to claim 2, wherein the layer forming the further waveguide region is patterned.

11. A junction structure according to claim 2, wherein the waveguide regions are in the form of rib waveguides.

12. A junction structure according to claim 2, wherein the silicon nitride layer is of sub-micron thickness and is less than one tenth the thickness of the silicon layer.

13. A junction structure according to claim 1 in which the said end face of the semiconductor waveguide at the junction is curved and forms a lens to direct transmitted light into the adjacent waveguide section.

14. An optical interferometer having parallel light transmitting paths, at least one of said paths including a waveguide junction structure as claimed in claim 1.

17. An interferometer according to claim 15, wherein the or each silicon waveguide is a rib waveguide formed from a silicon-on-insulator wafer.

18. An interferometer according to claim 15, wherein the insulating layer is silicon dioxide.

22. A method according to claim 20, wherein the second dielectric layer and the silicon nitride layer are deposited such that they also extend over the top surface of the semiconductor waveguide.

23. A method according to claim 19, wherein an anti-reflective coating is deposited over the end face of the semiconductor waveguide before the second dielectric layer is deposited.


25. A method according to claim 23 in which the end face is curved.
26. A method according to claim 20, wherein the first dielectric layer is patterned.
27. A method according to claim 20, wherein the semiconductor and first dielectric form a common integrated waveguide device.

REMARKS

Entry and consideration of this Amendment is respectfully requested.

Respectfully submitted,

SUGHRUE MION, PLLC
2100 Pennsylvania Avenue, N.W.
Washington, D.C. 20037-3213
Telephone: (202) 293-7060
Facsimile: (202) 293-7860
RJS/slb
Date: November 30, 2001


Robert J. Seas, Jr.
Registration No. 21,092

APPENDIX**VERSION WITH MARKINGS TO SHOW CHANGES MADE****IN THE CLAIMS:****The claims are amended as follows:**

3. A junction structure according to claim 1-~~or~~2, wherein the dielectric layer below the further waveguide region is silicon dioxide.
4. A junction structure according to claim 2-~~or~~claim 3, wherein the substrate comprises a layer of silicon dioxide and a layer of silicon.
5. A junction structure according to any of claims 2-~~to~~4, wherein the dielectric layer also extends over the light transmitting semiconductor layer.
7. A junction structure according to any of claims 2-~~to~~6, wherein there is provided an anti-reflective layer over said end face.
9. A junction structure according to claim 7-~~or~~claim 8, wherein the light transmitting semiconductor layer is directly covered by a layer of silicon dioxide on the side remote from the substrate.
10. A junction structure according to ~~any of~~claims 2-~~to~~9, wherein the layer forming the further waveguide region is patterned.
11. A junction structure according to ~~any of~~claims 2-~~to~~10, wherein the waveguide regions are in the form of rib waveguides.
12. A junction structure according to ~~any of~~claims 2-~~to~~11, wherein the silicon nitride layer is of sub-micron thickness and is less than one tenth the thickness of the silicon layer.

13. A junction structure according to ~~any one of the preceding claims 1~~ in which the said end face of the semiconductor waveguide at the junction is curved and forms a lens to direct transmitted light into the adjacent waveguide section.

14. An optical interferometer having parallel light transmitting paths, at least one of said paths including a waveguide junction structure as claimed in ~~any one of claims 1 to 13~~.

17. An interferometer according to claim 15 ~~or claim 16~~, wherein the or each silicon waveguide is a rib waveguide formed from a silicon-on-insulator wafer.

18. An interferometer according to ~~any of claims 15 to 17~~, wherein the insulating layer is silicon dioxide.

22. A method according to claim 20 ~~or 21~~, wherein the second dielectric layer and the silicon nitride layer are deposited such that they also extend over the top surface of the semiconductor waveguide.

23. A method according to ~~any of claims 19 to 22~~, wherein an anti-reflective coating is deposited over the end face of the semiconductor waveguide before the second dielectric layer is deposited.

25. A method according to claim 23 ~~or 24~~ in which the end face is curved.

26. A method according to ~~any of claims 20 to 25~~, wherein the first dielectric layer is patterned.

27. A method according to ~~any of claims 20 to 26~~, wherein the semiconductor and first dielectric form a common integrated waveguide device.

10 Rec'd PCT/PTO 30 NOV 2001

1

09/980021

WAVEGUIDE JUNCTION WITH SILICON NITRIDE

The present invention relates to junctions between semiconductor and dielectric waveguides. It relates for example to silicon nitride optical waveguides and in particular to the manufacture of junctions between such waveguides and silicon waveguides, and the use of such junctions, for example, in interferometers.

It is known in the art to provide a silicon on insulator waveguide connected to optical fibres, thus providing a path along which light can propagate. This type of waveguide is useful for many types of optical devices, including interferometers such as a Mach-Zehnder interferometer.

When light is transmitted through a silicon waveguide, some light energy is propagated as an evanescent field outside the geometric boundary of the silicon.

In the case of silicon, the evanescent field is small. The effective refractive index of the waveguide, and hence the phase velocity of any light transmitted through the waveguide, is dependent on the relative values of the refractive index in the material of the waveguide and the refractive index of the surrounding medium in which the evanescent field is propagated.

Silicon nitride may also be used for an optical waveguide in the same wavelength ranges as silicon. Silicon nitride has a lower refractive index than silicon and consequently variations in the refractive index of the surrounding medium have a much greater effect on the effective refractive index of a silicon nitride waveguide than is the case for a silicon waveguide. Consequently the use of silicon nitride can be advantageous in applications where sensitivity to variations in surrounding refractive index is required. Such use may be carried out in interferometers and particularly when used to detect the presence of selected external media as may occur in biosensing operations.

In use, one of two branches of the interferometers is immersed in the environment of interest whilst the other branch remains

in the control environment. The effect on the refractive index of the immersed branch can be measured by detection of the interference pattern formed with the light passing through the control branch, the degree of interference affecting the light intensity observed. This is because this intensity depends on the proportion of light maintained within the immersed branch, which in turn alters the effective length of the light path, which directly relates to the refractive index. The proportion of light maintained within the immersed branch depends on the relative difference of refractive index between the branch and its environment and therefore may be affected by, for example, a particular chemical.

However, silicon nitride is not readily formed as a thick enough layer for a waveguide having required structural integrity and thickness for accurate optical alignment with connecting optical fibres. Silicon nitride may also provide problems in single mode propagation if the waveguide is curved.

It is an object of the present invention to provide an improved optical waveguide including a silicon/silicon nitride junction.

According to a first aspect of the present invention there is provided a junction structure between a semiconductor waveguide region and a first dielectric forming a further waveguide region of lower refractive index than said semiconductor waveguide region, which structure comprises a light transmitting semiconductor layer having an end face at said junction, and a substrate below the semiconductor layer and extending beyond said junction and a first dielectric light transmitting layer formed over the extending part of the substrate and extending in alignment with the semiconductor layer to provide the further waveguide region, wherein a second dielectric layer of refractive index below that of the two waveguide regions is formed over the end face of the semiconductor and over the extending part of the substrate, thereby forming a support layer of required thickness for the further waveguide region to provide the required

alignment of the optical axis through the two waveguide regions.

According to a second aspect of the present invention there is provided an optical interferometer having parallel light transmitting paths, at least one of said paths including a waveguide junction structure as aforesaid.

According to a third aspect of the present invention there is provided a method of forming a junction structure between semiconductor and a first dielectric in an aligned region of a waveguide, the method comprising the steps of forming a semiconductor waveguide having an end face at said junction on a substrate below a light transmitting semiconductor layer, such that a substrate extension projects beyond said junction, depositing a layer of first dielectric to form a further waveguide region extending over said substrate extension and prior to depositing the first dielectric, depositing a second dielectric layer of refractive index below that of the semiconductor and the first dielectric so that said second dielectric extends over the end face of the semiconductor waveguide and over the substrate extension, thereby forming a support layer for the first dielectric over the substrate extension, the thickness of the said second dielectric layer providing the required alignment of the optical area through the waveguide.

According to a further aspect of the present invention there is provided a method of biosensing using the interferometer as aforesaid, comprising the steps of; measuring a first interference amplitude with the silicon nitride section exposed to a reference environment, and then exposing the silicon nitride section to a test environment, and measuring a second interference amplitude, and providing a sensing result from selective values of said first and second amplitudes.

An embodiment of the present invention will be described by way of example and with reference to the accompanying drawings in

which:

Figure 1 shows a sectional structure of a known silicon-on-insulator waveguide;

Figure 2 shows a junction between a silicon-on-insulator waveguide and a silicon nitride waveguide in accordance with the invention;

Figure 3 shows a plan view of a modification of the junction of Figure 2, and

Figure 4 shows an interferometer using a silicon and silicon nitride waveguide in accordance with the present invention.

In the figures, like reference numerals indicate like parts.

Integrated silicon rib waveguides of the type shown in Figure 1 are known. A light transmitting layer of silicon 1 is formed over a buried layer of silicon dioxide 2 on a silicon substrate 3. The silicon layer 1 has an upstanding rib 4 defining an optical transmission path along the waveguide. A layer of silicon dioxide 5 covers the silicon layer 1 and rib 4. The optical profile of light transmitted through the waveguide is shown schematically at 6 although there is an evanescent field which extends outside the silicon rib 4. Further details of this form of waveguide are given in a paper entitled "Low loss single mode optical waveguides with large cross-section in silicon-on-insulator" by J. Schmidtchen et al in Electronic Letters, 27, page 1486, 1999 and in PCT Patent Specification No. WO95/08787.

This form of waveguide provides a single mode, low loss (typically less than 0.2 dB/cm for the wavelength range 1.2 to 1.6 microns) waveguide typically having rib width and height dimensions in the order of 3 to 5 microns which can be coupled to optical fibres and which is compatible with other integrated components.

The speed of light along the waveguide, is dependent on the effective refractive index of the waveguide. This is dependent

on the refractive indices of both the silicon of the waveguide and the medium outside the waveguide through which the evanescent field travels. Silicon has a refractive index of about 3.5 whereas silicon nitride has a refractive index of only about 2. Consequently the effective refractive index of a waveguide using silicon nitride as the light transmitting medium is much more responsive to variations in the refractive index of the outside medium than is a silicon waveguide. Consequently, for applications of a waveguide responsive to variation of the external medium, silicon nitride provides advantages over silicon for the light transmitting layer. However, use of low pressure chemical vapour deposition (LPCVD) to deposit silicon nitride may result in a layer of thickness of the order of 0.2 μm whereas a typical silicon waveguide may conveniently have a thickness of about 4 μm . Such thin layers of silicon nitride in a waveguide present problems of structural integrity, single mode operation, as well as accurate alignment with any optical fibre system connected to the waveguide. Furthermore, silicon nitride in such a waveguide does not provide a basis for forming active devices which may respond to application of electric signals to vary the optical transmission in the way that silicon does.

For these reasons, the present embodiment shown in Figures 2 and 3 combines sections of silicon and silicon nitride in an optical waveguide with a junction between silicon and silicon nitride as shown in Figure 2.

The wafer of Figure 2 comprises the silicon-on-insulator waveguide 11 joined to a silicon nitride waveguide 12 at the junction 10 depicted as a sectional view in Figure 2. In this figure the direction of light travel is left to right. It may also be operated with light travel from right to left. The required optical alignment is achieved, which means that the centre of the light mode travelling through the silicon waveguide 11 is aligned with the centre of the light mode travelling through the silicon nitride waveguide 12. This achieves maximum light energy transfer across the junction. Approximate mode

field matching is achieved despite the large difference in size in the vertical direction between the waveguides due to the difference in refractive indices between the guides which compensates for the former effects. The optimum alignment position for the silicon nitride waveguide 12 is just below the centreline of the silicon waveguide 11 as detailed below.

The junction as shown in Figure 2 depicts a standard silicon-on-insulator waveguide 11 having an end face 13. A layer 14 of silicon nitride which acts as an anti-reflective coating covers oxide 5 on top of the rib 4. It also covers the end face 13 and the part of silicon oxide layer 2 which is not covered by the silicon waveguide 11 and forms an extension with the substrate 3 beyond the end face 13. On top of this layer is a deposited layer of silicon dioxide 16, and on top of this is a layer 17 of silicon nitride. The centre of the optical intensity profile through the silicon waveguide 11 and the silicon nitride waveguide 12 is indicated as a dotted line labelled reference numeral 18.

The formation of the junction and the alignment of the two waveguides will now be explained.

The silicon rib waveguide 11 is formed in the normal way according to the prior art but includes exposing an extension of the silicon substrate 3 and oxide layer 2 beyond the end 13 of the waveguide. Photolithography is used to selectively remove the oxide 5 from the waveguide end face 13. An anti-reflective silicon nitride layer 14 is deposited over the entire structure at a suitable thickness for maximum effectiveness at the transmission wavelengths required. In this embodiment the thickness is approximately $0.16\text{ }\mu\text{m}$. The next step is to measure the height of the silicon waveguide 11 to obtain the height of the centreline above the buried oxide layer 2. In this embodiment, the silicon waveguide has a height of $4.3\text{ }\mu\text{m}$ above the layer 2, which means the centreline would be at $2.15\text{ }\mu\text{m}$. However, the optimum height of maximum light energy in the

waveguide 11 is slightly lower than this at 1.84 μm . For other embodiments, the optimum height could be determined by simulation or testing. The next step is to deposit over the whole structure a layer of silicon dioxide 16 by PECVD. The thickness of this oxide 16 is carefully controlled to build up a bed over the extended substrate 3 and oxide 2 which has a thickness of 1.74 μm . This means that when the silicon nitride 18 is deposited at 0.2 μm thickness, also by PECVD, it forms a silicon nitride waveguide 12 with a centreline exactly in line with the height of maximum light energy within the silicon waveguide 11 at 1.84 μm above the buried oxide layer 2. Thus the maximum light energy is at line 18 throughout the junction and into the silicon nitride waveguide 12. The silicon nitride waveguide 12 can be patterned lithographically if desired, eg into a ridge or stripe structure.

Figure 3 shows a modified form of the junction in Figure 2 and similar reference numerals have been used for similar parts. In this case the junction is curved to form a convex lens structure at the end of the silicon waveguide 11 and a concave face on the silicon nitride 17 at the junction. The nitride layer 14 and oxide layer 16 each form a curved layer interposed between the convex end face of the silicon layer and the concave end face of the silicon nitride 17. The refractive index of the nitride layer 14 is less than that of the silicon layer 1 so that the curved interface acts as a composite cylindrical collimating lens focusing light in the horizontal plane.

In an alternative embodiment, the silicon oxide 16 and the silicon nitride 18 can be formed using thermal oxidation and LPCVD respectively. The heights of the layers could also be varied. A different dielectric could be used in place of the silicon oxide 16, such as silicon oxynitride or a polymer.

A silicon/silicon nitride waveguide of the type shown in Figure 2 or Figure 3 may be used in an interferometer, such as a Mach-Zehnder interferometer as shown in Figure 4. Such an

interferometer provides two parallel light paths 40 and 41 between a light source 42 and a light detector such as a photodiode 43. If a phase shift is introduced into the light transmitted by one of the paths relative to the other, either destructive or constructive re-combination may occur or be detected. The path 40 may be provided with a test window 44 for introducing a phase shift dependent on the external refractive index relative to the refractive index within the waveguide forming the part of the path adjacent the window 40.

In this example, the waveguide extending along the window 44 is formed of silicon nitride with a junction at each end 45,46 to a silicon waveguide as described with reference to Figure 2. The silicon waveguide at each end of the window, and that forming the path 41, may be joined in known manner to optical fibres leading to the detector 43 and from the source 42. A silicon waveguide with a 4 μm rib can be aligned with an optical fibre by undercutting the material which the waveguide is formed on to allow the optical fibre to be brought closer to the end of the waveguide as is disclosed in our US Patent 5787214. This would not be satisfactory with a waveguide of only 0.2 μm height and so the interposition of the silicon waveguides between the silicon nitride region and the optical fibres overcomes this problem.

The refractive index of silicon nitride is only 2, compared to 3.5 for silicon. This, together with the geometry used, results in a smaller fraction of the light being maintained within the waveguide. In the case of an interferometer for biosensing this is a useful property, because the waveguide is extremely sensitive to small concentrations of test substances around the sensing window. Furthermore, silicon nitride can be coated with various substances, so that the immediate surrounding of the sensing window can be used to induce a change in the effective refractive index. This is achieved by pre-coating the sensing window with a substance which is known to or expected to react with the substance under test. A typical example would be to coat it with a protein which is known to form a strong bond with

a particular antibody under test, before immersion in the test substance. If a bonding reaction takes place, the resulting biochemical structure has such a different structure from the protein coating alone that its refractive index is often very different from that of the protein coating alone. Therefore, the proportion of light energy transmitted outside the waveguide changes with the result that a different interference pattern is detected at the right-hand end of the waveguide. This indicates that the particular antibody is present in the test substance. Furthermore, the rate of change of refractive index can be monitored to give an indication of the speed of the bonding reaction. It is of course possible that the refractive index will be changed as soon as the sensing branch is immersed in the test substance even if no bonding reaction takes place, but in general the change is more pronounced if a reaction does take place.

Several of the structures described above can be formed on a single chip which could then be used to test several different substances at once. For example, the window 44 of each structure could be coated with a different protein but then each be immersed in a solution containing different antibodies in order to determine which antibodies are contained in the solution and at what concentration.

The silicon waveguide used in the reference path 41 may include a modified active region (eg a PIN diode) in which a variable electrical potential is applied to vary the amplitude of light transmitted through the waveguide. In this way, the electric field applied may be varied to maintain a constant light amplitude detectable by the light detector as the relative phases in the two paths varies. The light level selected may be one at which the detected amplitude variation with phase change has the steepest gradient thereby making the interferometer with maximum sensitivity to detection of phase change.

It will be understood that in the manufacture of the structure

shown in Figures 2 and 3 the steps of depositing the silicon nitride layers 14 and 17 involve blanket depositions over the entire area without the need for masking specific areas. Similarly the formation of the oxide layer 16 is a blanket operation over the entire area without the need for masking.

The nitride layer may be left as a blanket layer if the junction is curved to act as a lens as described above. Alternatively the nitride layer may be patterned to form a rib or ridge or a flat stripe.

CLAIMS:

1. A junction structure between a semiconductor waveguide region and a first dielectric forming a further waveguide region of lower refractive index than said semiconductor waveguide region, which structure comprises a light transmitting semiconductor layer having an end face at said junction, and a substrate below the semiconductor layer and extending beyond said junction and a first dielectric light transmitting layer formed over the extending part of the substrate and extending in alignment with the semiconductor layer to provide the further waveguide region, wherein a second dielectric layer of refractive index below that of the two waveguide regions is formed over the end face of the semiconductor and over the extending part of the substrate, thereby forming a support layer of required thickness for the further waveguide region to provide the required alignment of the optical axis through the two waveguide regions.

2. A junction structure between silicon and silicon nitride in a waveguide, which structure comprises a light transmitting silicon layer having an end face at said junction, and a substrate below the silicon layer and extending beyond said junction and a silicon nitride light-transmitting layer formed over the extending part of the substrate and extending as a further waveguide region in alignment with the silicon layer, wherein a dielectric layer of refractive index below that of silicon and silicon nitride is formed over the end face of the silicon between the silicon and the silicon nitride and over the extending part of the substrate, thereby forming a support layer of required thickness for the silicon nitride to provide the required alignment of the optical axis through the silicon nitride with the optical axis through the silicon.

3. A junction structure according to claim 1 or 2, wherein the dielectric layer below the further waveguide region is silicon dioxide.

4. A junction structure according to claim 2 or claim 3, wherein the substrate comprises a layer of silicon dioxide and a layer of silicon.

5 5. A junction structure according to any of claims 2 to 4, wherein the dielectric layer also extends over the light transmitting semiconductor layer.

6. A junction structure according to claim 5, wherein the silicon nitride layer also overlies the dielectric layer over the light transmitting semiconductor layer.

7. A junction structure according to any of claims 2 to 6, wherein there is provided an anti-reflective layer over said end face.

8. A junction structure according to claim 7, wherein the anti-reflective layer is silicon nitride.

9. A junction structure according to claim 7 or claim 8, wherein the light transmitting semiconductor layer is directly covered by a layer of silicon dioxide on the side remote from the substrate.

10. A junction structure according to any of claims 2 to 9, wherein the layer forming the further waveguide region is patterned.

11. A junction structure according to any of claims 2 to 10, wherein the waveguide regions are in the form of rib waveguides.

12. A junction structure according to any of claims 2 to 11, wherein the silicon nitride layer is of sub-micron thickness and is less than one tenth the thickness of the silicon layer.

13. A junction structure according to any one of the preceding claims in which the said end face of the semiconductor waveguide

at the junction is curved and forms a lens to direct transmitted light into the adjacent waveguide section.

14. An optical interferometer having parallel light transmitting paths, at least one of said paths including a waveguide junction structure as claimed in any one of claims 1 to 13.

15. An optical interferometer according to claim 14 in which said one of the paths includes a silicon waveguide having a section of its length in which the light transmitting layer is formed of a region of silicon nitride, a silicon to silicon nitride junction being formed at each end of said section and aligned with an optical path through the waveguide.

16. An interferometer according to claim 15, wherein each of the said paths includes a silicon waveguide formed by a light-transmitting layer of silicon on an insulating layer.

17. An interferometer according to claim 15 or claim 16, wherein the or each silicon waveguide is a rib waveguide formed from a silicon-on-insulator wafer.

18. An interferometer according to any of claims 15 to 17, wherein the insulating layer is silicon dioxide.

19. A method of forming a junction structure between semiconductor and a first dielectric in an aligned region of a waveguide, the method comprising the steps of:

forming a semiconductor waveguide having an end face at said junction on a substrate below a light transmitting semiconductor layer, such that a substrate extension projects beyond said junction;

depositing a layer of first dielectric to form a further waveguide region extending over said substrate extension and prior to depositing the first dielectric, depositing a second dielectric layer of refractive index below that of the

semiconductor and the first dielectric so that said second dielectric extends over the end face of the semiconductor waveguide and over the substrate extension, thereby forming a support layer for the first dielectric over the substrate extension, the thickness of the said second dielectric layer providing the required alignment of the optical area through the waveguide.

20. A method according to claim 19, wherein the semiconductor is silicon, the first dielectric is silicon nitride and said second dielectric layer is silicon dioxide.

21. A method according to claim 20, wherein the substrate comprises a layer of silicon dioxide over a layer of silicon.

22. A method according to claim 20 or 21, wherein the second dielectric layer and the silicon nitride layer are deposited such that they also extend over the top surface of the semiconductor waveguide.

23. A method according to any of claims 19 to 22, wherein an anti-reflective coating is deposited over the end face of the semiconductor waveguide before the second dielectric layer is deposited.

24. A method according to claim 20, wherein the anti-reflective coating is silicon nitride.

25. A method according to claim 23 or 24 in which the end face is curved.

26. A method according to any of claims 20 to 25, wherein the first dielectric layer is patterned.

27. A method according to any of claims 20 to 26, wherein the semiconductor and first dielectric form a common integrated waveguide device.

28. A method of biosensing using the interferometer of claim 15, comprising the steps of:

measuring a first interference amplitude with the silicon nitride section exposed to a reference environment, and then
5 exposing the silicon nitride section to a test environment, and measuring a second interference amplitude, and providing a sensing result from selective values of said first and second amplitudes.

10 29. A method according to claim 28 comprising the further step of:

prior to measuring the said first interference amplitude, coating the silicon nitride section with a substance comprising a first protein, wherein if the test environment comprises a second
15 protein, the second interference amplitude is dependent on the number of bonds formed between the first protein and the second protein.

30. A method according to claim 29, wherein one of the first
20 protein and the second protein is an antibody.

1/2

Fig.1.
PRIOR ART





Fig.2.



2/2

Fig.3.





Fig.4.



DECLARATION AND POWER OF ATTORNEY FOR UTILITY OR DESIGN PATENT APPLICATION (37 CFR 1.63)

As a below named inventor, I hereby declare that: My residence, mailing address, and citizenship are as stated below next to my name. I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

WAVEGUIDE JUNCTION WITH SILICON NITRIDE

the application of which

☐ is attached hereto

OR

☒ was filed on May 26, 2000 as United States Application Number or PCT International Application Number PCT/GB00/02028 (Confirmation No. _____), and was amended on _____ (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified application, including the claims, as amended by any amendment specifically referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56, including for continuation-in-part application(s), material information which became available between the filing date of the prior application and the national or PCT international filing date of the continuation-in-part application.

I hereby claim foreign priority under 35 U.S.C. 119(a)-(d) or (f), or 365(b) of any foreign application(s) for patent, inventor's or plant breeder's rights certificate(s), or 365(a) of any PCT international application(s) which designated at least one country other than the United States of America, listed below and have also identified below, by checking the box, any foreign application(s) for patent, inventor's or plant breeder's rights certificate(s), or any PCT international application(s) having a filing date before that of the application on which priority is claimed.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2

NAME OF SOLE OR FIRST INVENTOR:

Given Name

(first and middle [if any]) Andrew George

Family Name or Surname

RICKMAN

Inventor's Signature

Date

7 Jan 2002

Residence: City

Wilts

GB

State

Country UK

Citizenship

British

Mailing Address: St. Katherines Lodge, Savernake Forest, Marlborough, Wilts SN8 3NG

City

State

Zip

Country

UK

NAME OF SECOND INVENTOR:

Given Name

(first and middle [if any]) Arnold Peter Roscoe

Family Name or Surname

HARPIN

Inventor's Signature

Date

7/1/02

Residence: City

Oxford

GB

State

Country UK

Citizenship

British

Mailing Address: 58 Stratford Street, Oxford OX4 1SW

City

State

Zip

Country

UK